Int. J. Pres. Ves. & Piping **43** (1990) 433–442

Index

ABAQUS code, CANDU reactors, 243
ADINA (Automated Dynamic Incremental Nonlinear Analysis), IWM-CRACK, 259
Advanced Thermal Reactors
  LBB experiments, 39–55
  see also FUGEN
AGS *see* Annulus gas system
Ainsworth R6 method
  assessments and procedures, UK, 319–26
  circumferential crack stability, 129–47
    compared with GE-EPRI, 141–6
    failure assessment diagram, 133–4
    primary bending moment, 135
    recommendations, combined primary loadings, 146–7
    secondary bending moment, 136
    summary and conclusions, 147
Alloys
  alloy metal 182A, chemical composition, 274
  austenitic piping,
    break frequencies, 223
    IGSCC, 205
  Inconel, 167, 183
  MnMoNi-55, 221
  NiMoCr-37, 221
  Zircaloy-2, 2–3
American Society of Mechanical Engineers Boiler and Pressure Vessel Code Section XI,
  analytical *K*-solutions, 262
  flaw evaluation procedure, 335
  IWB-3600, 72
  IWB-3610, standard, 27, 30
  IWB-3640, 208
  IWB-3650,
    analysis, 341–4
    criterion, 329
  N-463 piping, 'Z-factor', 62
  Class 1 and 3 codes, LWR piping, 100
American Society for Testing and Materials
  A226, Japanese equivalents, 380–2
  A33, Japanese equivalents, 380–2
  A370, tensile tests, 275
  A508 Class 2 low-alloy steel, chemical composition, 274
  A516, Japanese equivalents, 380–2
  E813, J-values, 275
Annulus gas system
  CANDU,
    fuel channel, 230
    monitoring requirements, 429
  leak detectors, 233
  moisture detectability, 16–20
  PHT leakage, 5

Int. J. Pres. Ves. & Piping (**43**) (1990)—© 1990 Elsevier Science Publishers Ltd, England.
Printed in Great Britain

ASME *see* American Society of Mechanical Engineers
ATR *see* Advanced Thermal Reactors
Austenitic piping
  break frequencies, 223
  IGSCC, 205
Automated Dynamic Incremental Nonlinear Analysis (ADINA), IWM-CRACK, 259
Axial defects
  normalized burst pressure, 168–9
  surface flaws, ductile crack growth, 301–14
  in U bends, 171–2

Balance-of-plant nuclear piping
  LWR, 67–82
  pressurizer surge lines, 73
Battelle screening criterion, 371, 377
Bending
  effective bending stress, P_{eff}^{b}, defined, 208
  four-point test bend method, 368, 399–410
  primary/secondary bending moments, 134–6
Blunt notch compact specimens, 250–1
Boiling Water Reactor
  circumferential through-wall cracks, four-point bend test method, 399–410
  crack growth analysis, 104–9
    intensity factors, 390–2
  IGSCC, 205
  Japan, minimum detectable leak rate, 407
  least detectable crack length, 109
  minimum leak detection capability, 69
  results beyond design basis, 110
  Sweden, program, 205
BOP piping *see* Balance-of-plant nuclear piping
Bruce unit, operational flow, 200
Burst testing, steam generator tubes, 168
BWR *see* Boiling Water Reactor

Calandria tubes, Zircaloy-2, 2–3
CAN3-N285.4, code of practice, 24
Canada
  CAN3-N285.4, code of practice, 24
  leak-rate tests, through-wall artificial cracks, 413–24
Canada—*contd.*
  national programs, *see also* CANDU
  nuclear generating stations, Ontario Hydro, Darlington, 285–98
CANDU Owners Group, 425
CANDU reactor
  annulus gas system, monitoring requirements, 429
  description, 189–91
  3D finite element analysis, 241–2
  fuel channel, description, 2, 24
  LBB experience, 3–6
  LBB policies, 429, 430
  locating a leaking crack by safe simulation, 187–203
  maximum allowable leak rate, 416
  pressure tubes, 1–21, 23–36
    manoeuvres, simulation of crack growth, 202
    probabilistic approach to LBB, 229–38
  schematic diagram, 188
Canoe shape, crack growth, 301, 312
Carbon steel pipes
  crack growth analysis, 390
  fracture criterion, 379–96
    evaluation, 390–6
  LBB verification test and evaluations of crack growth, 379–96
  LWR, development of fracture criteria, 97–9
  prototypical test program, France, 155–62
  STS42, leak-rate tests, 399–410
  welded, fracture experiments, 329–49
  see also Stainless steel; Steels
CEA *see* France, Atomic Energy Commission
CEGB *see* UK Central Electricity Generating Board
Center-cracked panel test, 384
Chalk River active crack leak evaluation, simulation experiments, 193–9, 203
Channel outlet temperatures, 230–1
Charpy-V impact test, 257, 275, 276, 283
Charpy-V toughness, prediction, 88–9
Codes of practice
  CAN3-N285.4, 24
  NUREG, 1061, 68
  NUREG CR838, 88, 90
  see also ASME Boiler and Pressure Vessel Code
Cold-leg weld test, net-section-collapse analysis, 341–3

Consejo de Seguridad Nuclear, Spain, 85–92
Corrosion, pressure tubes, 59
Crack growth analysis
  boiling water reactors
  pressure water reactors, stress intensity factors, and, 390–2
    results, 107
    stress cycle, 104
  canoe shape, 301, 312
  circumferential through-wall cracks,
    acceptance criteria, 30
    Ainsworth R6 method, 137–40
    experiments, welded carbon steel pipes, 329–49
    Failure Assessment Diagram, 133–4
    Failure Assessment Line, 134
    flaw stability analysis, 60
    four-point bend test method, 368, 399–410
    GE-EPRI, 137–40
    LBB acceptance criteria, USNRC, 3.6.3 60–1
    leak detection rate, USNRC RG1.45 requirements, 89
    leak rate results, 75
    material classifications, 343
    plastic collapse exclusion, 28
    pressure water reactor pressurizer, 72
    stability
      Ainsworth method, R6 129–47
      GE-EPRI method, 129–47
    stability evaluation, 76
    stability *see* Ainsworth R6 method
    steam generator tubes, 169–70
    strength behaviour,
      calculational methods, 355–7
      pipes and materials, 353
      results, 354, 360–4
  ductile crack growth, axial surface flaws, 301–14
  longitudinal defects, 28–30
    calculational methods, 355
    pipes and materials, 353
    results, 357–60
    test results, 354
  model, MARATHON, 231–3
  net-section-collapse analysis, 341–3
  pressure water reactor
    results, 108
    stress cycle, 103
  through-wall cracks, DHC, 5, 15
Crack length, methods of estimation, 289
Crack mouth opening displacement, 369
Crack opening displacement
  area, steam generator tubes, 175–7
  artificial crack geometries, 415–16
  leak-rate test apparatus, 401, 415
Crack stability assessment
  FLET program, 73–7
  LWR, *see* loads, 80
  simplified method, 140–1
Crack tip opening displacement, 372
Cracks, *see also* Critical crack length; Flaws; Fractures
CRACLE *see* Chalk River active crack leak evaluation
Critical crack length
  delayed hydride cracking, 6–8
  initiation length, and instability length, 322
  leak rates, 15–16
  pressure vessels, 319
  time available for action, 8–15
Critical crack size, and leakage size crack, LWR, 77
Critical mass flux, 409
CSN *see* Consejo de Seguridad Nuclear

Darlington
  Ontario
    LBB test program, 285–98
    leak-rate tests, through-wall artificial cracks, 413–24
    NGS-A heat transport system, 113–26
      design features, 115–17
      mechanical loadings, 121
      pressure loadings, 119
      thermal loadings, 120
      vibration effects, 124–6
      water hammer effects, 124–6
DBE *see* Earthquake, design basis
DC-EP *see* Direct current electric potential
Deformation plasticity failure assessment diagram
  crack stability, 77–80
  FLET program, 77–8
DEGB *see* Double-ended guillotine break
Degraded Piping Program
  J-estimation, 159
  results, 341–9
Delayed hydride cracking
  controlled stimulation, CANDU reactors, 187–203
  critical crack length, 6–8
  defined, 3
  evaluation procedures, 25–34

Delayed hydride cracking—*contd.*
leak rates, 15–16
moisture detectibility, 16–20
principal features, 5
time available for action, 8–15
Dimensionless plastic-zone criterion, 345
Direct current electric potential method, onset of crack propagation, 369
Discussion, directed, 425–32
Double-ended guillotine break
as design criterion, 367
hypothetical, 67–8
DPFAD *see* Deformation plasticity failure assessment diagram
DPIII *see* Degraded Piping Program
Ductile crack growth of semi-elliptical surface flaws in pressure vessels, 301–14
Ductile fracture, properties for assessing LBB, 285–98
Duquesne Power Whipjet program, 335–6

Earthquake
design basis earthquake, loading, 123
seismic failures, 122–3
ECI *see* Emergency Cooling Injection signal
EDF *see* France, LBB applications
Effective bending stress, P_{eff}^{b}, defined, 208
Elastic-plastic failure
finite element models, nuclear pressure vessel, 258–70
Z-factor, 344
Elastic-plastic fracture mechanics
Ontario Hydro, 114–22, 285–98
tearing modulus analysis, 61
Electric discharge machining, 369
Electric Power Research Institute
computer codes, 73–7
GE-EPRI engineering approach, circumferential crack stability, 129–47
compared with Ainsworth R6 method, 141–6
prediction of fracture behaviour, 372–5
primary bending moment, 134
secondary bending moment, 135–6
J-estimation method, 159–61
net-section-collapse-theory, NP-192, 89
PICEP program, 413–24
Emergency Cooling Injection signal, 123
EPFM *see* Elastic-plastic failure mechanics
EPRI *see* Electric Poower Research Institute

FAD *see* Failure Assessment Diagram
Failure assessment curve, 393–6
Failure Assessment Diagram
CEGB method, 130
circumferential through-wall cracked cylinder, 133–4
Failure Assessment Line, 133
Fatigue, LBB limitations, 59
Fault tree, flow diagram of fracture assessment, 393
FEM *see* Finite element models
Ferritic weldments *see* Welds, ferritic
Finite element models
ABAQUS, 243
ADINA, 259
analysis, LWR, 104
CANDU reactors, 241–2
elastic-plastic failure, pressure vessel, 258–70
IWM-VERB, 267
MARC program, 390
nuclear pressure vessel, 258–70
Flaw evaluation
CEGB R6 method, 129–47, 319–26
CRACLE (Chalk River active crack leak evaluation), 193–9, 203
elastic-plastic fracture mechanics, 61, 114–22, 285–8
Failure Assessment Diagram, 133–4
Failure Assessment Line, 133
GE-EPRI engineering approach, 129–47, 372–5
proposed sequence, 27
structural integrity diagram, 319, 321, 324
Flaws
CANDU pressure tubes, 1–21, 23–36
circumferential *see* Crack growth analysis, circumferential through-wall cracks
critical-size *vs* leakage-size, 60–1
evaluation *see* Flaw evaluation
flaw size margin
LWR, 82
defined, 78
flaw stability analysis, USNRC, 61–4
longitudinal, 28–30
acceptance criteria, 30
elastic-plastic collapse excluded, 28
see also Crack growth analysis, longitudinal defects

Flaws—*contd.*
rolled joints, 41
strength behaviour,
calculational methods, 355–7
pipes and materials, 353
results, 354, 357–64
summary and conclusions, 364–5
FLET computer code, 73–7
Flow diagram of fracture assessment (fault tree), 393
Fluid choking, leak-rate, 419, 421
Four-point bend test method, circumferential through-wall cracks, 368, 399–410
Fractographic features, 293–5
Fracture analysis
evaluation flow, 97
finite element method, 99
flow diagram (fault tree), 393
vertification test, 98
Fracture experiments
A106 SMAW TWC pipe, 335–6
cold-leg SAW pipe, 330–5
dimensionless plastic-zone criterion, 345
elastic-plastic failure mechanics analyses, 345–9
fracture toughness test, 275, 277–8, 290–3
IWB-3650 analysis, 343–4
net-section-collapse analysis, 341–3
SAW carbon steel TWC, 406 mm, 338–41
SAW surface-cracked pipe, 406 mm, 337–8
welds, 329–49
Fracture toughness test
ASTM E1152, 290–3
ASTM E813, 275, 277–8
Fractures, *see also* Crack growth analysis; Critical crack length; Flaws
Framatome
LBB applications, 130
LBB in France, 151–62
France
Atomic Energy Commission, 152
LBB applications, 151–62, 165–79
liquid metal fast breeder reactors, 151
thermal stratification study program, 431
Fuel channel
CANDU reactor, 3
see also CANDU
FUGEN Advanced Thermal Reactors
description, 39–42
experimental loop, 47
FUGEN Advanced Thermal Reactors—*contd.*
LBB experiments, 44–55
leak detection system, 45
manufacture of pressure tubes, 42–4
results, 48–53
summary and discussion, 53–5

G-factor
expression, 394
LWR, defined, 99
typical pipe crack, 395
Gas annulus *see* Annulus gas system
Gas graphite reactors, 151
German-Kumar solution, unstable fracture analysis, 392
Germany
flawed pipes, strength behaviour, 351–65
KTA-Rule, 3201.2, 351
LBB policies, 429, 430
ductile crack growth of semi-elliptical surface flaws in pressure vessels, 301–14
pressure water reactors,
break exclusion requirements, 223–6
probabilities of leaks/breaks, 219–26
RSK concept, 115

Heat-affected zone (HAZ), welds, 273
Heaviside step function H, 210
Heavy-section steel technology program, 257
HSST *see* Heavy-section steel technology program

IGSCC *see* Inter-granular stress corrosion cracking
Inconel tubing
steam generator tubes, 167
600 M.A., 183
Inter-granular stress corrosion cracking
critical crack size, calculation, 206–9
failure probability, 205–16
input data, 210–13
probabilistic assumptions and analysis, 209–10
results, 213–14
sensitivenes and uncertainties, 214–16
summary and conclusions, 216
International Program on Piping Integrity Research Group, 154

Italy, stainless steel pipes, fracture behaviour, temperature studies, 367–77
IWM-CRACK, ADINA, 259
IWM-VERB, nuclear pressure vessel, 267
IWM-VERB program, 267

J-distributions, averaging, 247
J-estimation schemes *see* Ainsworth R6 method; Electric Power Research Institute, GE-EPRI
J-integral
  CEGB method, 130–1
  computation by different methods, 158–61
  contour dependence, 249
  defined, 28
  LWR, 70
  tearing modulus approach, 115
  variations along on crack front, 246–7
  virtual crack extension technique, 245–8
J–R curves
  base metal, 77
  finite element models, 258–9
  weld metal, 78
Japan
  boiling water reactors, leak-rate tests, four-point bend test method, 399–410
  carbon steel pipes,
    fracture criterion, 379–96
    LBB verification test and evaluations of crack growth, 379–96
  experimental study on fracture toughness, welds, 273–83
  FUGEN Advanced Thermal Reactors development plan, 39–55
  light water reactor, carbon steel piping components, development of criteria, 95–111
Jet impingement *see* Whipjet pipe test; Whipjet program
JIS STS49, chemical compoisition, 274

K-value *see* Stress intensity values
Kiss rolling operation, single/multiple cracks, 170–1, 177, 178

LBB policies
  crack growth rate, 6–7
  deterministic approach, 31–3
LBB policies—*contd.*
  dewpoint change of CO_2 gas, 49
  diagram, UK applications, 318
  experience, 35–6
  light water reactor,
    analysis, 71–2
    evaluation,
      crack stability, 106
      evaluation for conditions beyond design, 109–10
      method, 101–4
      postulated crack, 105
      results, 106–9
      sequence, 101
      summary, 110–11
    overview, 68–71
    sample calculations, 72–82
    summary and conclusions, 83
  probabilistic approach, 34
  time available for action, 8–15
  verification tests, Japan, 387–90
Leak detection
  capability, 34–5
  model, MARATHON, 233–4
Leak-rate tests
  Canada, 413–24
  constants used, 410
  critical crack length, 15–16
  fixtures, 414–16
  Japan, boiling water reactors, 399–410
  leak detection capacibility, leakage-size cracks, 71
  through-wall artificial cracks, 413–24
Leakage
  time availagle t_{LBB},
    calculation, 231–8
    cumulative distribution function, 234
Leakage size crack
  light water reactor, 82
    analysis, 71–82
Ligament instability curve, 319
Ligament rupture, 321
Light water reactors
  balance-of-plant nuclear piping, 67–82
  carbon steel pipes,
    fracture criterion, 379–96
    LBB verification test and evaluations of crack growth, 379–96
  flaw size margin, 82
  G-factor, defined, 99
  Japan, carbon steel piping components, development of criteria, 95–111
  LBB policies, 101–11
  load margin, 82

Liquid metal fast breeder reactors,
French plants, 151
LMFBRs *see* Liquid metal fast breeder reactors
Load margin, light water reactor, 82
LSC *see* Leakage size crack
LWR *see* Light water reactors

MARATHON
crack growth model, 231–3
examples, 234–7
leak detection model, 233–4
summary and discussion, 237–8
MnMoNi-55, ageing, 221
Moisture detectibility, 16–20
Monte Carlo techniques
CDF, 231
see also MARATHON

Net-section-collapse analysis, 341–3
welds, 342
Net-section-collapse criterion, calculations, 370–2
Newman–Raju solution, crack growth analysis, 392, 394
NiMoCr-37, ageing, 221
Notch impact energy, toughness indicator, 353, 355
NRC *see* USNRC
NSC *see* Net-section-collapse
NUPEC project, Japan, 95–111
NUREG 1061, LBB code, 68
NUREG CR-0838, teating modulus, 88, 90

Ontario Hydro *see* Canda; CANDU; Darlington, Ontario

Paris' power law, 390–2
PHT leakage, gas annulus, 5
PICEP *see* Pipe Crack Evaluation Program
Pickering unit
leak-simulation procedure, 199–200
pressure tube testing, 194
Pipe Crack Evaluation Program
computer code, 73–7
leak-rate tests, 413–24
Pipewhip restraints
elimination, pressure water reactor, 85–92
Pipewhip restraints—*contd.*
pressure tubes, 58
undesirability, 115
Plasticity correction, CEGB method, 132
Plugging criteria, steam generator tubes, 181–6
Plutonium-uranium mixed oxide fuels, 39
PRAISE code, 206
Pressure tubes
annealing of radiation damage, 8
CANDU reactor, 1–21, 23–36
corrosion, 59
crack length versus crack depth, 10
fatigue, 59
FUGEN Advanced Thermal Reactors, manufacture, 42–4
irradiation hardening, 8
loadings,
mechanical, 118
pressure, 118
thermal, 117–18
pipe whip restraints, 58, 85–92, 115
pressurizer surge lines BOP systems, 73
temperature gradient through wall, 10
water hammer, 59
Zr-2·5 Nb, 2
Pressure vessels
elastic-plastic finite element models, 258–70
extended safety analysis, 255–70
finite element models, 258–70
global vessel reaction, 262
IWM-VERB, 267
LBB assessment method, UK, 317–26
structural integrity diagrams, 319–24
tests,
dc potential drop method, 307
ductile crack growth, 305
geometry, material data and loading, 307
through-wall cracks, 322
wide plate fracture tests, 323
see also Pressure water reactors
Pressure water reactors
crack growth analysis, 103, 103–8
intensity factors, 390–2
degradation of steam generator tubes, Spain, 181–6
France, LBB applications, 153–4
Germany
break exclusion requirements, 223–6
probabilities of leaks/breaks, 219–26
least detectable crack length, 109
minimum leak detection capability, 69

Pressure water reactors—*contd.*
primary loop piping, elimination of pipe whip restraints, 85–92
results beyond design basis, 110
simulation tests, 353–4
steam generator tubes, LBB, 165–179
see also Pressure vessels
Primary looping *see* ASME standards
Primary water stress corrosion cracking, 184–5
Probabalistic Safety Assessment, WASH 1400, 205, 220
PWSCC *see* Primary water stress corrosion cracking

R6 method *see* Ainsworth method
Ramberg–Osgood equation, 373, 393
stress–strain curve, 131
Ramberg–Osgood parameters, 135
Ramberg–Osgood representation, 244, 246, 250–1
Reactor Coolant System Design, 184
Reactor pressure vessels *see* Pressure vessels
Reactors
operation, time available for action *t*, 201
see also Boiling water reactors; Light water reactors; Pressure water reactors
Reference stress concept, CEGB method, 132
Rolled joints
defects, 41
delayed hydride cracking, 3
effect of roll extension, 4
fabrication, 3
FUGEN Advanced Thermal Reactors, FL, DL, DU tests, 45–6
roll transition zone, instability criteria, 171
sandwich-type, residual stress distribution, 44
tensile hoop stresses, 3
Round Robin Test, 87

SA351 CF8A, fracture toughness, 89
Safe shutdown earthquake, 60
loads, light water reactor, crack stability, 77–80
SAW *see* Welds
Seismic failures, DBE, Darlington NGS-A heat transport system, 122–3
Simulation tests, pressure water reactor, 353–4
SMAW *see* Welds
Spain
pressure water reactor,
degradation of steam generator tubes, 181–6
pipe whip restraints, 85–92
SSE *see* Safe shutdown earthquake
Stable growth of cracks *see* Crack growth analysis
Stainless steel type 304, chemical composition, 274
Stainless steel 316L
fracture experiments, 369
properties, 323, 370
Stainless steel 316L-W
fracture experiments, 369
properties, 370
Stainless steel
DPFAD margin, 79–81
excessive load, stability evaluation, 81
fracture behaviour of pipes, temperature studies, 367–77
prototypical test program, France, 155–62
stability evaluation, 76
see also Carbon steel; Steels
Stainless steel SUS304, leak-rate tests, 399–410
Steam generator tubes
allowable leak rate, 177
crack opening area, 175–7
double cracks, 172–3
LBB, 165–79
maintenance, 166–7
multiple parallel cracks, 174–5
plugging criteria, 181–6
rupture criteria, 167–8
SLB, 185
summary and discussion, 178–9
tube support plate, cracks, 172
Steels
20 MnMoNi-55, J_R curves, 302
MnMoNi-55, ageing, 221
NiMoCr-37, ageing, 221
StE460, J_R curves, 302
see also Carbon steel; Stainless steel
Strain ageing
influence on fracture properties and welds, 295
MnMoNi-55, 221
NiMoCr-37, 221
Stress corrosion cracking, 59, 205–16

Stress intensity factor
  K-value analysis, 390–2
  surface cracks, 390–2
Stress intensity factor K_1, delayed hydride cracking, 25–6
Stress intensity factor K_{IH}, 6
Striping, defined, effects, 73
Structural integrity diagrams
  2·5 m plate width, 324
  50 m plate width, 324
  bounding defect sizes, 321
  factors to be considered, 319
Surface flaws
  axial defects, ductile crack growth, 301–14
  semi-elliptical, in pressure vessels, 301–14
  stress intensity factor, 390–2
  submerged-arc (SAW), 406 mm pipe, experimental results, 337–8
Sweden
  boiling water reactors, program, 205–16
  LBB policies, 430

Tearing modulus
  analysis, 61
  J-integral approach, 115
  NUREG CR-0838, 88, 90
Temperature studies, stainless steel pipes, fracture behaviour, 367–77
Tensile hoop stresses, rolled joints, 3
Tensile properties, *see also* Rambert–Osgood equation
Tensile test, 275, 276
Terminal Solid Solubility, exceeded, additional criteria, 30
TGI *see* Tungsten inert gas
Thermal loading, NGS-A heat transport system, Darlington, Ontario, 120
Thermal loadings, pressure tubes, 117–18
Thermal stratification, study program, France, 431
Through-wall cracks *see* Crack growth analysis, circumferential through-wall; longitudinal defects
Time available t_{LBB}, 201
  calculation, 231–8
  cumulative distribution function, 234
TSS *see* Terminal Solid Solubility
Tungsten inert gas welds, 370, 374

U bends, axial cracks, 171–2
UK Central Electricity Generating Board method
  double criteria, 130–1
  Failure Assessment Diagram, 130
  LBB assessment methods, 317–26
  plasticity correction, 132
  R6 procedure, Ligament Instability Curve, Critical Crack Length, 318–19
  reference stress concept, 132
United States
  fracture experiments,
    carbon steel welded pipes, 329–49
    elastic-plastic failure mechanics analysis, 345–9
  PICEP program, 413–24
  USNRC
    balance-of-plant nuclear piping, 67–82
    Degraded Piping Program, 154
    development of SRP3.6.3, 57–64
    flaw stability analysis, 61–4
    generic letter GL84.04, 86
    GL84.04, 86
    LBB acceptance criteria, 60–1
    LBB licensing, 57–8
    LBB policies, 429, 430
    leak detection guidelines, 432
  see also Electric Power Research Institute
Unstable fracture analysis, development of evaluation and criteria, 392–6
Upper-shelf notch impact energy, toughness indicator, 353, 355

VCE *see* Virtual crack extension
Vessels *see* Pressure vessels
Virtual crack extension technique, *J*-integral, 245–8

WASH 1400, Probabilistic Safety Assessment, 205, 220
Water hammer effects
  Darlington NGS-A heat transport system, 124–6
  excessive dynamic loads, 59
Wedge-open-loaded specimens, 257
Weigh balance water supply system, 416–17
Welds
  alloy metal 182A, chemical compoisition, 274
  base metal stress-strain curves, 74

Welds—*contd.*
cold-leg weld test, net-section-collapse analysis, 341–343
ferritic
ductile fracture properties for assessing LBB, 285–98
welded pipe versus net-section-collapse, 342
fracture experiments
carbon steel pipes, 329–49
toughness of weld metals in steel piping, 273–83
gas tungsten arc welds, 273, 287
heat-affected zone (HAZ), 273
influence of strain ageing on fracture properties, 295
net-section-collapse analysis, 342
Ontario Hydro weld procedures, 287
PN-107 and PN-229, shielded metal-arc (SMAW) and submerged-arc (SAW) processes, 286
PN-108 and PN-232, post-weld heat treatment, 286
post-weld heat treatment, 286
procedures, Ontario Hydro, 285–98
shielded metal-arc (SMAW), 88
A106 Grade B, TWC pipe, 330, 335–6
carbon steel pipes, LBB verification test and evaluations of crack growth, 379–96
TWC pipe, A106 Grade B, experimental results, 335–6
specifications, light water reactor, 70
stress corrosion cracking, analysis, 208
submerged-arc (SAW), 88
406 mm pipe, surface-cracked, experimental results, 337–8
Welds—*contd.*
submerged-arc (SAW)—*contd.*
carbon steel pipes, LBB verification test and evaluations of crack growth, 379–96
cold-leg pipe section, experimental results, 330–5
TWC 406 mm pipe, experimental results, 338–41
tungsten inert gas, 370, 374
weld metal 308L, chemical composition, 274
weld metal stress-strain curves, 75
Whipjet pipe test, net-section-collapse analysis, 341–3
Whipjet program, Duquesne power, 335–6

Z-factor
elastic-plastic failure, 344
limit load analysis, 61–2
Zahoor formula, 394
Zircaloy-2, calandria tubes, 2–3
Zr pressure tubes, leak detection and location, 191–2
Zr-2·5Nb
crack rate growth,
data, irradiated/unirradiated, 7
temperature dependence, 6
pressure tubes, 2
critical crack length, 191
DHC, 189–91
flaw evaluation methodology, 25–34
FUGEN Advanced Thermal Reactors, critical crack length, 55
LBB experiments, 39–55
stress intensity factor K_{IH}, 6